



TruWood[®] SIDING

TRUWOOD CEDAR SHAKE LAP SIDING

When only the look of cedar will do, TruWood Cedar Shake Lap Siding offers an alternative that's beautiful, rugged and cost-effective. You won't find any checks, cracks or surface variations in our TruWood Cedar Shake 7/16 in and 1/2 in Lap Siding. What you will find: the distinctive look of hand-split cedar shakes with a beautiful, finished appearance that lasts. Our Cedar Shake Lap Siding offers Tru character, Tru wood appeal and smooth, uniform paint application. No defects, hassles or high costs. Just Tru beauty.


FEATURES/BENEFITS

- Quality engineered surface and core
- 30-year limited warranty
- Pre-primed for improved weatherability
- 16 ft lengths
- Choice of self-aligning or bevel profile
- Matching reversible TruWood Trim
- Installs 25-40% faster than cement or vinyl sidings
- Use for residential single-family and multi-family housing, remodeling and light commercial projects
- Ask us about our FSC[®] products




- Endures extreme weather conditions in the toughest climates
- Resists mildew, rot and termite damage
- Naturally-occurring additive safe for use around children and pets

BEVELED EDGE
CEDAR SHAKE
7/16 in LAP SIDING



SELF-ALIGNING
CEDAR SHAKE
1/2 in LAP SIDING



SPECIFICATIONS:

| Lap Size | Pc/ Unit | Pc/ Bundle | Bundles/ Unit | Sq. Ft./ Unit | Maximum Exposure in inches | Approx. Coverage Sq. Ft./ Unit | Sq. Ft. Needed To Cover 1,000 Sq. Ft. of Wall Area* | Approx. Weight Lbs./Unit |
|-----------------------------|-------------|---------------|------------------|------------------|----------------------------------|---|--|--------------------------------|
| 7/16 in x 10-1/2 in x 16 ft | 168 | 6 | 28 | 2,352 | 9-1/2 | 2,020 | 1,162 | 3,900 |
| 1/2 in x 10-1/2 in x 16 ft | 140 | 5 | 28 | 1,960 | 9-1/2 | 1,685 | 1,162 | 3,900 |

*Allows for a 1 in overlap and assumes a 5% waste factor.

TruWood Siding and Trim meet the requirements of the following:

2015 International Building Code
2015 International Residential Code
ICC ESR-2588
Federal Manufactured Housing Standards
American National Standard ANSI-CPA 135.6 - 2015
California Wildland-Urban Interface (WUI)

CAL. PROP 65 WARNING: Use of this product may result in exposure to wood dust, known to the State of California to cause cancer.

Fire rating = Class C, R Value = 0.67 (hour) (Sq. Ft.) (Fahrenheit) per BTU
1/2 in Lap Siding = No Shear Value
The approximate weight: 7/16 in Lap Siding = 1,660 Lbs./MSF
The approximate weight: 1/2 in Lap Siding = 1,980 Lbs./MSF
TruWood Lap Siding is shipped 12 units per truckload or 40 units per railcar

FOR YOUR NEAREST DISTRIBUTOR, COMPLETE INSTALLATION INSTRUCTIONS, MAINTENANCE, SERVICE AND WARRANTY INFORMATION, GO TO TruWoodSiding.com. FOR LOCATIONS, CALL **800.417.3674** OR EMAIL truwood@collinsco.com.

