



TruWood®
SIDING | TRIM

TRUWOOD CEDAR SHAKE LAP SIDING

When only the look of cedar will do, TruWood Cedar Shake Lap Siding offers an alternative that's beautiful, rugged and cost-effective. You won't find any checks, cracks or surface variations in our TruWood Cedar Shake 1/2 in. Lap Siding. What you will find: the distinctive look of hand-split cedar shakes with a beautiful, finished appearance that lasts. Our Cedar Shake Lap Siding offers Tru character, Tru wood appeal and smooth, uniform paint application. No defects, hassles or high costs. Just Tru beauty.


FEATURES/BENEFITS

- Quality engineered surface and core
- 30-year limited warranty
- Pre-primed for improved weatherability
- 16 ft. lengths
- Self-aligning feature for ease of installation
- Matching TruWood Trim
- Installs 25-40% faster than cement or vinyl sidings
- Use for residential single-family, multi-family housing, remodeling and light commercial projects
- Easy and safe to install using normal woodworking tools. No silica dust.
- Ask us about our FSC® products (FSC®-C002971)



- Resists mildew, rot and termite damage
- Naturally-occurring additive safe for use around children and pets

**SELF-ALIGNING
CEDAR SHAKE
1/2 in. LAP SIDING**



SPECIFICATIONS:

Lap Size	Pc./ Bundle	Pc./ Unit	Maximum Exposure in inches	Sq. Ft. Coverage Per Piece	Approx Coverage Sq. Ft./ Unit	Sq. Ft. Needed To Cover 1,000 Sq. Ft. of Wall Area	Approx. Weight Lbs./Unit
1/2 in. x 10-1/2 in. x 16 ft.	5	140	9-1/2	12.67	1685	1161	3700

* Allows for a 1 in overlap and assumes a 5% waste factor.

TruWood Siding and Trim meet the requirements of the following:

2023 International Building Code
2023 International Residential Code
ICC ESR-2588
American National Standard ANSI-CPA 135.6 - 2012
California Wildland-Urban Interface (WUI) Approved

Fire rating = Class C
R Value = 0.67 (hour) (Sq. Ft.) (Fahrenheit) per BTU
1/2 in. Panel Siding = No Shear Value

CAL. PROP 65 WARNING: Use of this product may result in exposure to wood dust, known to the State of California to cause cancer.

PROPER STORAGE AND HANDLING

- Store siding flat and support on stringers to avoid sagging and contact with the ground
- Siding must be covered and protected from the elements
- Stack no more than eight units high
- Allow siding to acclimatize to local conditions prior to installation

TO FIND YOUR NEAREST DISTRIBUTOR, WARRANTY INFORMATION, INSTALLATION INSTRUCTIONS, CARE AND MAINTENANCE INSTRUCTIONS, A SIDING CALCULATOR, OR TO VIEW OUR PRODUCTS ON SAMPLE HOMES USING OUR VISUALIZER TOOL, HEAD TO **TruWoodSiding.com**. CAN'T FIND WHAT YOU NEED? **800.417.3674**

